

# EPC-B2000



<b>System</b>	<b>CPU</b>	Intel® Core™ i3-10100(T)E Intel® Core™ i5-10500(T)E Intel® Core™ i7-10700(T)E
	<b>Chipsatz</b>	Intel® H420E
	<b>Memory</b>	up to 64GB ECC RAM (2x 32GB)
	<b>Storage</b>	2x 2,5" SSD/HDD
	<b>GPU</b>	Intel® UHD-Grafik 630
	<b>Display</b>	1x LVDs, 1x DP, 1x HDMI
	<b>Ethernet</b>	2x RJ45 Gigabit Ethernet LAN
	<b>Front I/O Panel</b>	4x USB 3.0 4x COM
	<b>Rear I/O Panel</b>	1x 230V Power in 1x DP 1.2 (DP++) 1x HDMI 2.0 2x LAN 100/1000 (1x I210AT, 1x I219LM) 4x USB 3.2 1x Audio (Mic-in, Line-out, Line in)
<b>PCle</b>	1x PCIe x16 (Gen3) LP	
<b>Environment</b>	<b>Operating Temperature</b>	0 – 40 °C
	<b>Humidity</b>	10 ~ 85% @ 40 °C, non-condensing
	<b>Vibration (5 ~ 500 Hz)</b>	1 Grms
	<b>Shock</b>	10 G (with 11 ms duration, half sine wave)
	<b>IP</b>	-
<b>Cooling</b>	<b>Chassis Fan</b>	2 (7 cm/39.45 CFM)
	<b>Air Filter</b>	-
<b>Power Supply</b>	<b>Power Supply</b>	150W 80+ Silber
<b>Physical Characteristics</b>	<b>Dimension (HxBxT)</b>	98 x 250 x 255 mm
<b>OS</b>	<b>Windows</b>	Windows 10 Pro / IoT
	<b>Linux</b>	Linux 64-bit
<b>Optional</b>		Front Com and USB
<b>Available</b>		2030