

FWA-1012VC



System	CPU	Intel® Atom® C3558 (-4CA1S) Intel® Atom® C3758 (-8CA1S)
	QAT Technology	Yes
	Memory	up to 64GB RAM (2x 32GB)
	Storage	1x M.2 2280 SATA SSD
	Console	1x RJ45 port
	Display	NA
	Ethernet	4x 1G RJ45 (-8CA1S) / 6x 1G RJ45 (-8CA1S) 2x 1G SFP
	Front I/O Panel	-
	Rear I/O Panel	2x USB 3.0 1x Power Button 4x LAN 100/1000 / 6x LAN 100/1000 2x LAN SFP 1x Console RJ45 1x 12V DC Power in 2x Sim Socket
Environment	Operating Temperature	0 – 40 °C with 0.7m/s air flow
	Humidity	10 ~ 95% @ 40 °C, non-condensing
	Vibration (5 ~ 500 Hz)	1 Grms
	Shock	10 G (with 11 ms duration, half sine wave)
	IP	-
Cooling	Chassis Fan	1 / 2
	Air Filter	-
Power Supply	Power Supply	12V DC 5A, 60W
Physical Characteristics	Dimension (HxBxT)	44 x 250 x 193 mm
OS	Windows	-
	Linux	Linux 64-bit
Optional		LTE WiFi/BT Rackmount Kit Wallmount Kit PoE
Available		2029